



Access control kit for one door. The kit consists of metal enclosure with transformer and networked access controller. The controlled door can be managed on both, read-in and read-out sides, by RS485 (MCT series readers), RACS CLK/DTA (PRT series readers) or Wiegand readers.

Door lock and readers are supplied from the controller's onboard supply outputs capable to deliver respectively 0.2 A and 1.0 A. Entire system is supplied from the mains transformer included in the kit.

Features:

- access control kit for one door
- read-in/read-out door control
- MC16-PAC-1 networked access controller
- interface to 4 RACS CLK/DTA readers (PRT series)
- interface to 4 Wiegand readers
- supply output 0.2 A
- supply output 1.0 A
- 0.3 A battery charging current
- deep battery discharge protection
- 18 V/40 VA transformer
- tamper contact
- space for 7 Ah battery
- metal enclosure
- dimensions (external):
255.0 x 255.0 x 90.0 mm (height x width x thickness)

Order guide	
<i>Item</i>	<i>Description</i>
MC16-PAC-1-KIT	1-door access control kit; ME14-40VA metal enclosure; MC16-PAC-1 access controller module

Legal Notice

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevA © 2017 ROGER sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the www.roger.pl