



The UT-4 interface enables communication with various devices equipped with RS232 serial port through a computer network. The device is equipped with serial port which can be configured as RS232, RS422 or RS485 and with 10/100 Mb/s Ethernet port for communication within computer network.

**Features:**

- power supply 10-15 VDC
- average current consumption 75 mA
- maximum current consumption 150 mA
- LAN/WAN 100/10Mbit/s operation
- static or dynamic IP address
- Virtual Serial Port can be configured in the device and it can be used in RACS 4 system or third party applications
- plastic enclosure adapted for installation on flat surface e.g. wall
- advanced Digi Connect ME module from Digi Corp
- environmental conditions of operation:
  - temperature from 0°C to +55°C
  - humidity from 10% to 95%
- dimensions: 68.0 x 100.0 x 35.0 mm (height x width x thickness)
- weight: ≈110.0 g
- CE mark

**Ordering guide**

| <i>Item</i> | <i>Description</i>                   |
|-------------|--------------------------------------|
| <b>UT-4</b> | RS232/RS485/RS422-Ethernet interface |

**Legal Notice**

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevB © 2021 ROGER sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the [www.roger.pl](http://www.roger.pl)