



Expander with six relays, each with NO/10 A/230 VAC/
30 VDC contact, RACS CLK&DTA communication inter-
face, DIN rail plastic enclosure.

Features:

- power supply 12 VDC
- average current consumption 20 mA (plus 40 mA per each activated relay)
- six relay outputs with single NO/10 A/230 VAC/30 VDC max load
- RACS CLK/DTA communication protocol
- DIN rail plastic enclosure
- 6900 VA maximum switching power (AC1 category)
- distance between controller and XM-6DR module up to 150 m
- environmental conditions of operation:
 - temperature from -25°C to +60°C
 - humidity from 10% to 95%
- dimensions: 85.0 x 62.0 x 73.0 mm (height x width x thickness)
- weight: ≈125.0 g
- CE mark

Ordering guide

<i>Item</i>	<i>Description</i>
XM-6DR	Expander with six relays; each with NO/10 A/230 VAC/30 VDC contact

Legal Notice

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevB © 2021 ROGER sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the www.roger.pl