



The MCT80M is an access terminal dedicated to RACS 5 access control and building automation system. Terminal enables identification of users by means of 13.56 MHz MIFARE Ultralight® and MIFARE® Classic cards. MCT80M is equipped with RS485 interface which is used for communication with access controller. Be-

cause of its relatively small size, reader can be also used as locker/cabinet reader. MCT80M can be installed in outdoor locations without any additional protection measures. The MCT80M is aligned with QUADRUS series product line.

Features:

- access terminal for RACS 5
- 13.56 MHz MIFARE Ultralight/Classic reader
- 3 LEDs
- buzzer
- RS485
- tamper
- outdoor environment
- QUADRUS product line design
- dimensions: 100.0 x 45.0 x 16.0 mm (height x width x depth)
- CE mark

Ordering guide

<i>Item</i>	<i>Description</i>
MCT80M	Access terminal; 13.56 MHz MIFARE Ultralight/Classic; supply 12 V; QUADRUS series design

Legal Notice

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevC © 2023 Roger sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the www.roger.pl